

# DI-5B42 2-Wire Transmitter Interface Modules

## FEATURES

- Isolated +20VDC Current Loop Supply
- Provides Isolation for Non-isolated 2-wire Transmitters
- High Level Voltage Output: +1V to +5V
- 1500Vrms Transformer Isolation
- ANSI/IEEE C37.90.1-1989 Transient Protection
- Input Protected to 240VAC Continuous
- 100dB CMR
- 100Hz Signal Bandwidth
- $\pm 0.05\%$  Accuracy
- $\pm 0.02\%$  Linearity
- CSA Certified
- Mix and Match DI-5B Types

## DESCRIPTION

Each DI-5B42 2-wire transmitter interface module provides a single channel which accepts a 4 to 20 mA process current input and provides a standard +1 to +5V output signal (see block diagram). An isolated +20VDC regulated power supply is provided to power the current transmitter. This allows a 2-wire loop powered transmitter to be directly connected to the DI-5B42 without requiring an external power supply. The regulated supply will provide a nominal +20VDC at a loop current of 4mA to 20mA.

The DI-5B42 will provide a 1500V isolation barrier for non-isolated 2-wire field transmitters. It can also be used when additional isolation is required between an isolated 2-wire transmitter and the input stage of the control room computer.

The voltage output is logic switch controlled, which allows these modules to share a common analog bus without the requirement of external multiplexers.

The DI-5B modules are designed with a completely isolated computer side circuit which can be floated to  $\pm 50V$  from Power Common, pin 16. This complete isolation means that no connection is required between I/O Common and Power Common for proper operation of the output switch. If desired, the output switch can be turned on continuously by simply connecting pin 22, the Read-Enable pin to I/O Common, pin 19.

A precision  $20\Omega$  current conversion resistor is supplied with the module. All field inputs are fully protected from accidental connection of power-line voltages up to 240VAC. The module has a 3dB bandwidth of 100Hz.

Signal filtering is accomplished with a six-pole filter, with two poles on the field side of the isolation barrier, and the other four on the computer side.


## SPECIFICATIONS

Typical at  $T_A = +25^\circ C$  and +5V Power

		<b>DI-5B42</b>
Input Range		4mA to 20mA
Input Resistor	Value Accuracy Stability	20.00 $\Omega$ $\pm 0.1\%$ $\pm 10\text{ppm}/^\circ C$
Loop Supply Voltage		Nominal 20V at 4mA to 20mA
Isolated Excitation Protection		240Vrms max ANSI/IEEE C37.90.1-1989
Input Protection		240Vrms max ANSI/IEEE C37.90.1-1989
CMV, Input to Output		1500Vrms max ANSI/IEEE C37.90.1-1989
CMR (50Hz or 60Hz)		100dB
NMR (-3db at 100Hz)		120db per decade above 100Hz
Accuracy*		$\pm 0.05\%$ Span $\pm 4\mu A$ RTI
Nonlinearity		$\pm 0.02\%$ Span
Stability	Input Offset Output Offset Gain	$\pm 1\mu V/^\circ C$ $\pm 40\mu V/^\circ C$ $\pm 25\text{ppm}/^\circ C$ of reading
Noise	Input, 0.1Hz to 10Hz Output, 100kHz	10nArms 500 $\mu$ Vrms
Bandwidth, -3dB		100Hz
Response Time, 90% Span		4ms
Output Range		+1V to +5V
Output Resistance		50 $\Omega$
Output Protection		Continuous Short to Ground
Output Selection Time (to $\pm 1\text{mV}$ of $V_{out}$ )		6 $\mu$ s at $C_{load} = 0$ to 2000pF
Output Current Limit		$\pm 20\text{mA}$ max
Output Enable Control		Max Logic "0"            +0.8V Min Logic "1"            +2.4V Max Logic "1"            +36V Input Current, "0,1"      0.5 $\mu$ A
Power Supply Voltage		+5VDC $\pm 5\%$
Power Supply Current		180mA at load of 20mA 100mA at load of 4mA
Power Supply Sensitivity		$\pm 10\mu V/\%$ RTI*
Mechanical Dimensions		2.28" $\times$ 2.26" $\times$ 0.60" (58mm $\times$ 57mm $\times$ 15mm)
Environmental		Operating Temperature    -40 $^\circ C$ to +85 $^\circ C$ Storage Temperature      -40 $^\circ C$ to +85 $^\circ C$ Relative Humidity          0 to 95% Noncondensing RFI Susceptibility $\pm 0.5\%$ Span Error at 400MHz, 5W, 3ft
*Includes nonlinearity, hysteresis and repeatability; RTI=Referenced to Input.		

# DI-5B42 2-Wire Transmitter Interface Modules

## Block Diagram



## Ordering Information

Model Number	Input Range	Output Range
DI-5B42-01	4mA to 20mA	+1V to +5V



241 Springside Drive  
Akron, Ohio 44333  
330-668-1444

### Data Acquisition Product Links

(click on text to jump to page)

[Data Acquisition](#) | [Data Logger](#) | [Chart Recorder](#) | [Thermocouple](#) | [Oscilloscope](#)

The information on this data sheet is subject to change without notice.

DATAQ and the DATAQ logo are registered trademarks of DATAQ Instruments, Inc. All rights reserved. Copyright © 2005 DATAQ Instruments, Inc.